



NOTE:
 ALL DIMENSIONS IN INCHES AND SUBJECT TO CHANGE WITHOUT NOTICE
 ** = RT-4 FOR SJ6009
 30" AND 36" DIA. TANKS WILL REQUIRE A 11"x15" MWY WHEN CEMENT OR PRE-KRETE LINED

OPTIONS:

- INTERIOR LINING:
 - NONE (390F MAX.) WITH CARBON STEEL FITTINGS, FPT
 - GLASS (160F MAX.), UP TO 8 ft. LONG TANK
 - WITH CARBON STEEL FITTINGS, FPT
 - WITH 304 S.S. FITTINGS, FPT
 - CEMENT (180F MAX.), DIA 30" TANK AND ABOVE WITH 304 S.S. FITTINGS, FPT
 - PREKRETE (350F MAX.), DIA 30" TANK AND ABOVE WITH 304 S.S. FITTINGS, FPT
 - OTHER _____
- SUPPORTS:
 - PIPE LEGS, SET
 - PIPE LEGS W/ PADS, SET (SHOWN)
 - OTHER _____

COVER DRAWING FOR SJ SERIES TANK

JOB : _____

QTY. REQ'D.: _____ SO#: _____

REP.: _____

ENG.: _____

SPECIFICATIONS:

MODEL : ACE "SJ" STORAGE TANK
 CONFORMS TO : ASME CODE, SECTION VIII, DIV.1
 RATING : 150 PSI @ 390F
 SHELL / HEADS : CARBON STEEL

-B- O.A.H.	-ØA- TANK DIAMETER, inches										
	CAPACITY	18	24	30	36	42	48	54	60	66	72
-C- SHELL LENGTH, feet	02	36" 36 GAL.									
	03	48" 49 GAL.									
	04	60" 62 GAL.	63" 117 GAL.	66" 190 GAL.	69" 275 GAL.	72" 390 GAL.	75" 510 GAL.				
	05	72" 75 GAL.	75" 140 GAL.	78" 225 GAL.	81" 325 GAL.	84" 460 GAL.	87" 605 GAL.	90" 740 GAL.	93" 940 GAL.	96" 1155 GAL.	99" 1405 GAL.
	06		87" 163 GAL.	90" 260 GAL.	93" 375 GAL.	96" 530 GAL.	99" 700 GAL.	102" 860 GAL.	105" 1085 GAL.	108" 1330 GAL.	111" 1615 GAL.
	07		99" 186 GAL.	102" 295 GAL.	105" 425 GAL.	108" 600 GAL.	111" 795 GAL.	114" 980 GAL.	117" 1230 GAL.	120" 1505 GAL.	123" 1825 GAL.
	08				117" 475 GAL.	120" 670 GAL.	123" 890 GAL.	126" 1100 GAL.	129" 1375 GAL.	132" 1680 GAL.	135" 2035 GAL.
	09								141" 1520 GAL.	144" 1855 GAL.	147" 2245 GAL.

HEAD DEPTH	D	6"	7 1/2"	9"	10 1/2"	12"	13 1/2"	15"	16 1/2"	18"	19 1/2"
CONN. SIZE	M	1 1/2"	1 1/2"	2"	2"	2"	3"	3"	3"	3"	3"
LOCATION	E	---	---	---	---	14"	14"	14"	16"	16"	16"
INSPECT. OPENING	E	1 1/2"	1 1/2"	2"	2"	12"x16" MANWAY	12"x16" MANWAY	12"x16" MANWAY	12"x16" MANWAY	12"x16" MANWAY	12"x16" MANWAY
RETURN	G	14"									
(QTY) LEG CPLG.	N	(3) 1 1/2"	(3) 1 1/2"	(3) 1 1/2"	(3) 1 1/2"	(4) 2"	(4) 2"	(4) 2 1/2"	(4) 2 1/2"	(4) 2 1/2"	(4) 2 1/2"
TANK CLEAR.	K	8"	8 1/2"	11"	9 1/2"	13 1/2"	12"	10"	9"	10"	9 1/2"

NOMINAL DIMENSIONS & CAPACITIES SHOWN



CERTIFIED BY
ACE HEATERS

SHELL _____ PSI @ _____ °F
 TUBES _____ PSI @ _____ °F
 MIN. D.M.T. _____ °F @ _____ PSI
 S/N _____ YEAR BUILT _____
 MODEL _____
 CAPACITY _____ GAL SA. _____
 JOB NO. _____ XXX _____

ACE HEATERS

This document contains proprietary information from ACE HEATERS. Do not reproduce or distribute without prior written consent of ACE HEATERS.

ASME Section VIII Div 1:
 Design Pressure: 150 psig
 Test Pressure: 195 psig (150 psi / glass)
 Max Design Temperature: 390°F

A.I.:

SCALE: NA Filename: SJ TANK - COVER DRAWING SHEET 1 OF 1
 Dwg By: _____ Orig Date: _____ Rev Date: _____ Checked By: _____

SEC. VIII DIV1, 150 PSI SJ TANK, COVER DRAWING
 VERTICAL - PIPE LEGS WITH OR WITHOUT PADS

Dwg #: SJ-A-V020 SO: _____ REV A04